

# BAUHAUS MOVEMENT

Precision / Progression

Modular Tile

**Construction**

Tufted, Textured Loop

**Tile Size**

50 cm x 50 cm (19.7" x 19.7")

**Face Fiber**

Milliken-Certified Nylon 6.6

**Antimicrobial**

AlphaSan® AF Built-In Protection

**Tufted Face Weight**

16 oz/yd<sup>2</sup> (543 g/m<sup>2</sup>)

**Dye Method**

Solution Dyed

**Gauge**

1/12

**Stitches**

10

**Tufts**

120 /in<sup>2</sup> (1,858/100 cm<sup>2</sup>)

**Standard Backing**

PVC-Free B2™ Hard Back

**Density Factor**

215,944

**Recyclability**

100%

**Nominal Total Thickness**

0.28" (7.1 mm)

**Nominal Total Weight**

103.5oz/yd<sup>2</sup> (3,510 g/m<sup>2</sup>)

**Flammability (Radiant Panel  
ASTM-E-648)**

≥ 0.45 (Class I)

**Smoke Density (NFPA-258-T or  
ASTM-E-662)**

≤ 450

**Methenamine Pill Test (CPSC FF-1-70  
or ASTM D 2859)**

Self-Extinguishing

**Lightfastness (AATCC 16E)**

≥ 4.0 at 80 Hours

**Crocking (AATCC 165)**

≥ 4.0 Wet or Dry

**Static Electricity (AATCC-134) 20%  
R.H., 70° F.**

≤ 3.5 KV, Permanent Conductive Fiber

**Texture Appearance Retention Rating  
(TARR)**

Heavy Traffic End-Use Applications

**Indoor Air Quality—CRI Green Label  
Plus™**

GLP3200, Carpet Category 14X

**Recommended Installation Method(s)**

Monolithic; Ashlar; V.Ashlar

**WARRANTIES**

- 15-year Face Fiber Wear
- 15-year Antistatic
- 15-year Floor Compatibility
- 15-year Color Pattern Permanency
- 15-year Floor Release

- 15-year Moisture Resistance
- 15-year Delamination of Backing
- 15-year Dimensional Stability
- 15-year Tuft Bind
- 15-year Edge Ravel

- Flammability
- 15-year Antimicrobial Protection (AlphaSan®)

This hard-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

