## illiken.

## LANDMARK

## Artifact

Modular Tile

Construction

Tufted, Textured Loop

Tile Size

1 m x 1 m (39.4" x 39.4")

Yarn Type

Milliken-Certified WearOn® Nylon Type 6.6

Stain Resist / Soil Release

StainSmart®

Dye Method

PrintWorks™ Precision Dyeing

**Tufted Face Weight** 

 $15 \text{ oz/yd}^2 (508.6 \text{ g/m}^2)$ 

Gauge

1/12

Stitches Per Inch

98

**Tufts** 

117.6/in<sup>2</sup> (1,821/100 cm<sup>2</sup>)

**Finished Pile Height** 

0.13" (3.30 mm)

**Finished Pile Thickness** 

0.08" (2.03 mm)

**Average Density (Finished)** 

6,541

**Standard Backing** 

PVC-Free WellBAC® Comfort Cushion Available with TractionBack®

**Recycled Content by Total Weight** 

Standard Backing: 39.3% Pre-Consumer, 0.0% Post-Consumer NSF 140 Platinum Backing Option: 28.6% Pre-Consumer, 10.7% Post-Consumer

**Embodied Carbon** 

 $14.37 (kg CO_2 e)/m^2$ 

**Nominal Total Thickness** 

0.28" (7.1 mm)

**Nominal Total Weight** 

 $89.2 \text{ oz/yd}^2 (3,024 \text{ g/m}^2)$ 

Flammability (Radiant Panel

**ASTM-E-648**)

≥ 0.45 (Class I)

**Smoke Density (NFPA-258-T or** 

**ASTM-E-662)** 

≤ 450

**Methenamine Pill Test (CPSC FF-1-70** or ASTM D 2859

Self-Extinguishing

**Lightfastness (AATCC 16E)** 

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H.,70° F.

≤ 3.5 KV, Permanent Conductive Fiber

**Texture Appearance Retention Rating** 

Severe Traffic End-Use Applications

**Recommended Maintenance** 

MilliCare® Textile and Carpet Care Service Network

Indoor Air Quality—CRI Green Label

Plus™

GLP0793, Carpet Category 5Y

Recommended Installation Method(s)

Monolithic

## WARRANTIES

Lifetime Face Fiber Wear Lifetime Antistatic Lifetime Floor Compatibility Lifetime Color Pattern Permanency Lifetime Floor Release

Lifetime Cushion Resiliency Lifetime Moisture Resistance Lifetime Delamination of Backing Lifetime Staining/Soiling (StainSmart®) Lifetime Dimensional Stability

Lifetime Tuft Bind Lifetime Edge Ravel Flammability













This cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

