

OBEX™ BAR: MONO

Entrance Flooring

BAR PLANK

Bar Material

Extruded Aluminum Profile with high density polyethylene foam base layer

Plank Size

27.6 cm x 100 cm (10.87" x 39.4")

Total Nominal Thickness

11 mm (0.43")

Bar Color

Aluminum (silver)

Planks Per Box

7 planks, 20.8 ft² (1.93 m²)

TEXTILE

Construction

Tufted, Cut Pile

Yarn Type

ECONYL® Nylon Monofilament

Dye Method

Solution Dyed

Tufted Face Weight

18.9 oz/yd² (640 g/m²)

Recycled Content by Total Weight

17.8% Pre-Consumer,
8.0% Post-Consumer

Nominal Total Weight

26.1 oz/ft² (7,959 g/m²)

Flammability (Radiant Panel

ASTM-E-648)

≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or

ASTM-E-662)

≤ 450

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Loading Weight

11,023 lbs (5,000 kg)

Rolling Load Limit (ASTM F2753)

No noticeable deformation or damage to the structural integrity with a 400 pound per wheel at 2,500 cycles with load applied to a 200 mm diameter, 32 mm wide rubber tread castor.

Temperature Resistance

-22°F to +122°F (-30°C to +50°C)

Recommended Maintenance

Daily Vacuum, Deep Clean via Hot Water Extraction

Recommended Installation Method(s)

Ashlar for Recessed or Surface installs

Installation Zone Application

Zone 1 or Zone 2

ADA / BS8300 / ISO 21542 Compliant

WARRANTIES

1 Year Manufacturing Defect Warranty

5 Year Wear Warranty



Find us in

MasterSpec®

Powered by Deltek Specpoint®