

VARIATIONS 2.0 (Aida & Bargello)



SPECIFICATION

Construction	Tufted, Textured Loop
Face Fiber	100% Milliken-Certified Nylon 6
Tile Size	50 cm x 50 cm (19.7" x 19.7")
Dye Method	Solution Dyed
Tufted Face Weight	15 oz/yd ² (509g/m ²)
Average Density	8,626
Gauge	1/10
Stitches	10.9
Tufts	104/in ² (1,599/100 cm ²)
Standard Backing	PVC-Free WellBAC™ Function Available with TractionBack®
Recyclability	100%
Recycled Content By Total Weight	0% Post Industrial
Nominal Total Thickness	0.22" (5.6MM)
Nominal Total Weight	90 oz/yd ² (3,052g/m ²)


PERFORMANCE

Antimicrobial	AlphaSan® AF Built-In Protection*
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours
Crocking (AATCC 165)	≥ 4.0 Wet or Dry
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber
Texture Appearance Retention Rating (TARR)	Heavy
Indoor Air Quality—CRI Green Label Plus™	GLP3200, Carpet Category 14X

WARRANTIES

Lifetime Face Fiber Wear
Lifetime Antistatic
Lifetime Floor Compatibility
Lifetime Color Pattern Permanency
Lifetime Floor Release
Lifetime Antimicrobial Protection (AlphaSan®)
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Dimensional Stability
Lifetime Tuft Bind
Lifetime Edge Ravel
Lifetime Flammability

INSTALLATION METHOD



3RD PARTY CERTIFICATES



Design Copyright - Milliken & Company. This carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.