



PRIMA RIGIDFORM™ LVT

Strike a balance with embossed textures and acoustic features.

The Prima collection elevates the look of resilient flooring through a precision embossed texture and rich color palette that evokes natural hardwood. The RigidForm™ construction with attached pad layer provides exceptional acoustics with single step installation for premier Hospitality projects.

- EMBOSSED IN REGISTER (EIR)
- FIVE TACTILE WOOD DESIGNS
- NATURAL RANGE OF COLOR
- TWO PRACTICAL PLANK SIZES

- M/PACT™ CARBON NEUTRAL PRODUCT
- HEAVY COMMERCIAL WEAR LAYER WITH 20-YEAR WARRANTY
- NO ADDITIONAL UNDERLAYMENTS OR ADHESIVE NEEDED



CLASSIC Champion
7" x 48" planks: CLM98
9" x 60" planks: CLL98



CLASSIC First Rate
7" x 48" planks: CLM10
9" x 60" planks: CLL10



CLASSIC Peerless
7" x 48" planks: CLM122
9" x 60" planks: CLL122



GRADIENT Eminent
7" x 48" planks: GRM176
9" x 60" planks: GRL176



GRADIENT Foremost
7" x 48" planks: GRM211
9" x 60" planks: GRL211



GRADIENT Ideal
7" x 48" planks: GRM217
9" x 60" planks: GRL217



GRADIENT Supreme
7" x 48" planks: GRM235
9" x 60" planks: GRL235



NOUVEAU Elite
7" x 48" planks: NVM76
9" x 60" planks: NVL76



NOUVEAU Select
7" x 48" planks: NVM206
9" x 60" planks: NVL206



NOUVEAU Top Class
7" x 48" planks: NVM44
9" x 60" planks: NVL44



SERENITY Paramount
7" x 48" planks: SRM204
9" x 60" planks: SRL204



SILK Distinctive
7" x 48" planks: SKM121
9" x 60" planks: SIL121



SILK Five star
7" x 48" planks: SKM15
9" x 60" planks: SIL15

SHADE VARIANCE



PRIMA LVT RIGIDFORM™

Construction

High Performance Rigid Core Tile

Wear Layer Thickness

22 mil (0.56 mm)

Overall Thickness

5.0 mm (0.2")

Finish

ProGuard™ Coating

Tile Size

7.56" x 48.62" (192 mm x 1235 mm)
9.13" x 60.31" (232 mm x 1532 mm)

Warranty

Limited Light Commercial (Multifamily units
& Hospitality rooms only)
22 mil (5.0 mm) - 20 Years

Weight Per Box

7.56" x 48.62": 44.8 lb (20.32 kg)
9.13" x 60.31": 47.0 lb (21.32 kg)

Quantity Per Box

7.56" x 48.62": 25.52 ft² (2.37 m²)
9.13" x 60.31": 26.78 ft² (2.49 m²)

Cartons Per Pallet

7.56" x 48.62": 48
9.13" x 60.31": 45

Pallets Per Container

7.56" x 48.62": 20
9.13" x 60.31": 21

Acoustics - Meets minimum Hotel Acoustic Requirements (ASTM E492)

Tested material 8" concrete slab. IIC Rating:
56 (6" no drop ceiling)
59 (8" no drop ceiling)
51 (18" OWT with ceiling)

Recommended Installation Method(s)

Random



SUSTAINABLE FEATURES

Milliken LVT is durable resilient flooring engineered with the highest quality raw materials to provide unsurpassed performance and enduring aesthetics. Milliken LVT is 100% phthalate free. All production waste is granulated and recycled into backing production to create an internal closed loop recycling process.

Milliken LVT meets many environmental standards, including FloorScore® certified, Prop 65 Free and Phthalate Free, Certified EPD, and Declare.

