

# Nature Supply

Forest Rain/Forest Sound

## SPECIFICATION

Construction	Tufted, Textured Loop
Face Fiber	100% Milliken-Certified Nylon
Tile Size	9.8" x 39.4"(25cm x 100cm)
Dye Method	Solution Dyed
Gauge	1/12
Stitches	9.144
Tufts	109.7/in <sup>2</sup> (1,699/100 cm <sup>2</sup> )
Standard Backing	PVC-Free WellBAC™ Function Available with TractionBack®
Recyclability	100%
Recycled Content By Total Weight	6.9% (4.4% Post Industrial, 2.5% Post Consumer)
Nominal Total Thickness	0.21" ( 5.3mm)

## PERFORMANCE

Antimicrobial	AlphaSan® AF Built-In Protection*
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours
Crocking (AATCC 165)	≥ 4.0 Wet or Dry
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber
Texture Appearance Retention Rating (TARR)	Heavy
Indoor Air Quality—CRI Green Label Plus™	GLP3200, Carpet Category 14X

## WARRANTIES

Lifetime Face Fiber Wear
Lifetime Antistatic
Lifetime Floor Compatibility
Lifetime Color Pattern Permanency
Lifetime Floor Release
Lifetime Antimicrobial Protection (AlphaSan®)
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Dimensional Stability
Lifetime Tuft Bind
Lifetime Edge Ravel
Lifetime Flammability

## INSTALLATION METHOD



Plank

## 3<sup>RD</sup> PARTY CERTIFICATES



Declare.

Design Copyright – Milliken & Company.

This carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Customer Service 8621 61455588 | millikencarpet.com  
© 2020 Milliken & Company | Made in China